

Solidtronic

ST-RoIP4+D/W/R-PTT360PRO

Standalone RoIP Gateway

STAY EFFICIENT BY KEEPING CONNECTED ON MULTIPLE DEVICES



PoC-COS/COR PTT Control Technology



Radio-COS/COR PTT Control Technology



iDats-4 PTT Control Technology



ADF-2 For 2-Way Radio Repeater System



End of TX Roger Beep Alert for Radio Channel



Stable Bandwidth Ethernet Connection



Support Different Brand & Model Radios



www.comm360.biz

enquiries@comm360.biz



SPECIFICATIONS

Power Supply	DC 5V
Power Consumption	600mA (Typical)
Network Interface	Ethernet 10/100Base-T
CPU	ARM
Display	4.3" Touch Screen LCD
Control Buttons	MENU and BACK
Communication App	PTT360Pro
Interoperability Activation Time	0.2 Second (Typical)
Digital Interoperability Stabiliser	0.2 Sec or 2 Seconds Selectable
Dimensions	Desktop Type: 510g (Typical) Wall Mount / Rack Mount Type: 530g (Typical)
Weight	Desktop Type: 175 (W) x 95 (D) x 38 (H) mm Wall Mount / Rack Mount Type: 205 (W) x 95 (D) x 38 (H) mm
AC Adapter	Input: AC100~240V Output: DC5V 2A

ACCESSORIES

			
ST-M26-COS/COR	ST-IM25-COS/COR	RT-M12	ST-M16-COS/COR
			
ST-HYTMD7-COS/COR	ST-IMA1X0	ST-KM25-COS/COR	RK-KM8

DISCALIMER: Specifications and product details are subject to change without prior notice. Solidtronic strives to ensure the accuracy of the information presented, but we do not warrant or guarantee the completeness or correctness of the content. Customers are encouraged to verify product specifications and availability with Solidtronic representatives.

For detailed specifications and inquiries, please contact us via email at enquiries@comm360.biz